



## SPEC MIX BRICKLAYER 500® 2008 RULES & GUIDELINES

KEEP GOING. KEEP MOVING. KEEP WORKING.™



### General Instructions & Guidelines

1. During the competition, the competitors' work methods in the SPEC MIX BRICKLAYER 500® shall be as close as possible to an actual jobsite situation.
2. The bricklayer must lift all his own bricks and trowels of mortar from no more than 5 mortar boards and 5 stacks of bricks placed as seen fit on the working side of the wall. These stacks of boards must be set out along the length of the wall in usual working fashion by the bricklayer's tender.
3. The tender must be provided by the bricklayer. No more than 1 tender will be allowed for each bricklayer.
4. Any assistance from the tender or others in placing bricks or tools in the bricklayer's hand or transferring mortar from the mortar boards to the wall will result in disqualification.
5. The contestant's tender will set up each contestant's work area utilizing five mortar boards and five stacks of brick following the configuration of the contest exactly.
6. Contestants can select location, orientation and size of brick stacks and location of mortar boards once the contest starts.
7. The bricklayer is responsible for raising his own line blocks and lines at each end of the wall; securing line and pins/corner blocks, and for running each course of bricks. The use of metal, timber or other profile posts, prepared story poles, levels marked for heights or stopped ends are to be excluded.
8. Contestants will need to furnish their own tools for the competition. This includes all hand tools.
9. Contestants will be allotted ample time prior to the competition to place the starter courses of block and starter course of brick.
10. Upon completion of the competition, competitors will have a 10 minute rest period followed by 10 minutes to finish the working side of the wall and the ends (NOT the backside). Competitors will be allowed to use any standard masonry tool to finish the working side of the wall. Joints are to be struck with a round (U) joint finish. Water and any other liquids or cleaning agents are not allowed to be used to finish the wall.
11. Length of the contest will be (60) sixty minutes followed by the 10 minute rest period and 10 minute striking period.

### Materials & Construction of Contest Wall

1. Wall will be constructed utilizing running ½ bond pattern with return ends.
2. The wall will be approximately 8" wide, constructed 2 brick deep. The width of the wall can be slightly modified at the option of the contestant to accommodate for the depth of the brick utilized for the competition.

3. Two courses of block will be used as base course with the top course laid face shell up. Upon competitor's preference, both courses of block may be laid face shell up to aid in leveling the base courses.
4. One double wythe course of modular (2 1/4" x 3 5/8" x 7 5/8") brick will be placed on the starter block as a brick starter course. This brick will not be counted in the contest.
5. Brick will weigh no less than 3 lbs.
6. Length of the wall will be 26 ft on 1/2 running bond (39 brick long per side), adjustable as needed based on the length of the brick utilized for the competition.
7. Mortar will be cut flush. There is no jointing during the laying portion of the contest. Joints will be finished on the working side and ends of the wall in the finishing portion of the contest.
8. Brick must be laid overhand on back wall.
9. Mortar will be supplied by SPEC MIX, Inc.
10. Wall must be completed so each wythe is within 2 courses of each other. Units laid beyond this tolerance will not be counted in the final brick count.

### **Quality Standards**

1. The top surface of the last full double wythe course laid is to be checked for height. The height tolerance over the wall length will be +/- 1/4" or less and will be measured by taking a height measurement on each end and in the middle of the wall on the working side to the last completed double wythe. Competitors will set a pin to mark the points of measure for judging on each end and in the middle on the working side of the wall before the competition starts in the mortar joint under the starter course of brick. Judges will average the 3 height measurements. Each individual measurement cannot vary by more than +/- 1/4" from that average. Failure to meet any or all height points within the tolerance laid out in this standard will result in a 100 brick deduction in the final brick count.
2. Both ends and the face of the wall must be within 1/4" or less of being truly vertical. This will be judged using the mason's level at 4 plumb points at each end of the wall and one plumb point in the middle of the working side of the wall for a total of 9 plumb points. Failure to meet any or all plumb points within the tolerance laid out in this standard will result in a 100 brick deduction in the final brick count.
3. All mortar bed and head joints must be cut flush on both sides of the double wythe wall during the 60 minute bricklaying portion of the contest. Failure to make an honest attempt to cut the mortar joints flush as laid out in this standard will result in a 100 brick deduction in the final brick count.
4. The wall will be allowed no more than 20 voids for the entire project. This will be judged using an S-Jointer. Upon visual inspection, if there appears to be a void, the judge will attempt to tool the head joint and bed joint. If the void can be reasonably filled, it will not be counted as a void. Exceeding 20 voids will result in a 100 brick deduction in the final brick count.
5. Brick in the wall must be laid face shell out. Brick with chips greater in size than 1/2" in diameter are not to be used in the competition. Lipped brick in the wall must be less than 1/4". Brick lipped beyond 1/4" in or out of the wall, greater than 1/2" size brick chips and brick laid face shell in will each result in a 100 brick deduction for each criteria in the final brick count.
6. Mortar joint thickness tolerance for bed joints are not less than 1/4" or greater than 1/2". If there are any bed joints less than 1/4" or greater than 1/2", a 100 brick deduction in the final brick count will be assessed.

7. Mortar joint thickness tolerance for head joints are not less than 1/8" or greater than 3/4". If there are any head joints exceeding 3/4" or less than 1/8", a 100 brick deduction in the final brick count will be assessed.
8. The premise of the SPEC MIX BRICKLAYER 500 is to construct a finished quality wall containing as many units as possible in one hour following the rules set forth in this document.
9. First, second and third place will be awarded to the masons who have laid the first, second and third highest brick count in the contest meeting the quality standards and after subtracting any deductions set forth in the SPEC MIX BRICKLAYER 500 competition rules.
10. The SPEC MIX TOP CRAFTSMANSHIP winner will be determined by first narrowing the field down to competitors who have laid at least 500 brick and have not had any quality standard deductions. If there are no competitors who have laid at least 500 brick with no deductions, the total count will be dropped from 500 to 400 with no deductions to determine the craftsmanship winner. If there are no competitors with at least 400 brick and have no deductions, then the eligible contestants will be those who have laid 500 brick with one quality standard deduction. If there are no competitors with a minimum of 500 brick and only one quality standard deduction, the count will be dropped to 400 and one quality standard deduction to determine the eligible craftsmanship award contestants. Then a majority of Judges will subjectively come to agreement on the wall that they feel is the most sellable through visual inspection. If more than one eligible wall is determined to be equal in quality by the judges, the wall with the higher brick count will be awarded the SPEC MIX TOP CRAFTSMANSHIP Award. This is a subjective award and the Judges decision in determining the winner is final and is not disputable by the competitors or their representatives.

